

Latexfalt[®] Coldfix Mortar Coarse

Product description	Latexfalt Coldfix Coarse Floor Repair is a pre-mixed mortar, based on a cement-stable emulsion and selected chippings.
Uses	For repair approx. 8 mm thick and over, such as: <ul style="list-style-type: none">- Repair of worn concrete floors and joints- Making repairs/levelling floors, drives or for filling ruts- Filling holes, pot-holes and other damage in cement-bonded floors, asphalt floors, etc.
Pre-treatment	The surfaces to be laid or repaired must be free of dirt, dust, grease, old coating layers or loose particles. Then brush in a liberal coat of a mixture of 1 part bonding emulsion (from tub supplied) to 1 part water (coverage approx. 0,2 kg undiluted emulsion per m ²). Do not allow this bonding coat to dry, but apply the Latexfalt Coldfix Floor Mortar immediately.
Application	1 part by volume Portland cement Class A 10 parts by volume Latexfalt Coldfix Floor Repair Mortar Mix the cement with a little water. Add this to the measured quantity of Latexfalt Coldfix Floor Repair Mortar. Add more water if necessary to produce a mix which is easy to work but not too wet. Mix until an even, grey-black colour is obtained. Apply the mortar, then compact and finish with a steel skimmer. Once mixed with cement, the mortar must be applied within 1 hour. Coverage: approx. 10 litre per m ² at a thickness of 1 cm.
Drying time	Depending on thickness and drying conditions, Latexfalt Coldfix repairs can be rapidly subjected to loads again (1-3 days). Once completely hardened they have a compressive strength of approx. 30 kg/cm ² .
Storage	Store frost-free, in sealed packaging, for a maximum of 6 months.
Safety	Latexfalt Coldfix Floor Repair Mortar contains no solvents and is non-toxic.

The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

23-02-2006



Hoogewaard 183 Postbus 6 2396 ZG Koudekerk aan den Rijn

Tel.071-341 91 08 Fax.071-341 59 46

E-mail:info@latexfalt.com www.latexfalt.com