

# Latexfalt® Floorwax [ black]

<b>Properties</b>	Latexfalt Floorwax is a solvent-free emulsion on a wax basis, containing anion active and non-ionogenic tensides, preservative components, synthetics and additives. Latexfalt Floorwax maintains and protects the floor and dries to a glossy film.
<b>Instructions</b>	The old wax coating must be removed as completely as possible before the new wax is applied. Rinse the floor with clean water after cleaning and allow to dry. Then apply the Latexfalt Floorwax with a suitable wax applicator. After the first coat has dried, a thin second coat can be applied if required.
<b>pH-value</b>	8
<b>Quantity</b>	As required for the type of the floor: 1 litre for 10 to 20 m <sup>2</sup> . Always apply Latexfalt Floorwax thinly and evenly.
<b>Subsequent maintenance</b>	For normal soiling, vacuum clean with a brush attachment. For excess dirt, wash with a mop or use a scrubbing vacuum cleaner.
<b>Safety</b>	Not to be taken internally. Non-flammable and no dangerous vapour.
<b>Colours</b>	Transparent and black.
<b>Storage</b>	Store free of frost.

The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

