

Flexkote

Emulsion	Flexkote is a bitumen emulsion modified with natural fillers.
Composition	After drying Flexkote creates a protecting toplayer with optimal adhesion to Elastofalt EP, roofing felts and concrete.
Uses	Recoverable and preventative maintenance, protecting against moisture, dirt and soil salts. Used as a pre-coating where acrylic roofing paints are prescribed.
Pre-treatment	The surface to be treated must be free of dust, oil and grease.
Application	Flexkote can be applied by employing a brush, roller or squeegee.
Coverage	For use of a protected coating on Elastofalt EP, one layer of 1 kg/m ² meter is necessary. For use as a protective coating on concrete foundations and roofs, more layers of 1 kg/m ² are preferred, depending on the quality of the concrete and the expected time of protection.
Restrictions	<ul style="list-style-type: none">- the user must not harm the system in any case;- the user must not spill solvent or oil on the system and- not to use fire, welding, chemicals etc. which will harm the system;- if in doubt the user should contact the distributor prior and after the job.- the product must be used according to this application sheet.

The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

